



A-88N

Superlative Performance With Servo Motor Driven

Description

A-88N is designed for various applications and able to work with different strap widths, wide tension range as well as rapid strapping speed with servo motor driven.

Diversity of assist functions is all as standard equipped.

Features

- Looping ejector
- Short feeding sensor
- Coil end eject system
- Electronic tension control
- Waist auto loading system
- Run on 5,6,9,12,15 mm strap
- Highest performance (over 60 straps/min.)

Options

- Top press - P
- Various arch sizes
- Stainless steel housing (A-88M)

Specification

Speed (straps / min)	60 up
Strap width (mm)	5,6,9,12,15 specified
Tension range for 5,6mm	3~30kgs
Tension range for 9,12,15mm	5~70kgs
Standard arch (W x H mm)	650 x 500
Motor	Servo
Sealing method	Heating element
Table height (mm)	805
Power supply	110/220/230/240V, 50/60Hz, 1PH 220/230/380/415/440V, 50/60Hz, 3PH
Power consumption (kw)	1.2
Layout dimension (L x W x H mm)	1230 x 580 x 1430

*Specification subject to change without notice



JIA-IN INDUSTRY CO., LTD.

T +886 4 2359 4966

F +886 4 2359 2449

E info@joinpack.com

www.joinpack.com

