



A-93AR

Fully Automatic Strapper with Roller Driven Table

Description

Ideal designed to integrate by IN-LINE with other machines for general industry. Various arch size combination and workability of different strap widths between 9 ~ 15 mm can serve all kinds of packages.

Tension range between 15~70 KGs and cycles speed 24 straps.

Available to equip with various unique options to perform advanced functions.

Features

- Proximity cam switch
- Instant heating system
- Stainless-clad steel roller
- Weld cooling time adjustable
- Hinged power roller driven table top
- Up-stream and down-stream interlock
- Heating temperature from 230°C~460°C for PP & PET straps

Options

- Looping ejector
- Top press function
- Auto loading system
- Stack light with buzzer
- Coil end strap ejecting out
- Stainless steel housing. (SUS#304)

Specification

Speed (straps / min)	24
Strap width (mm)	9,12,15 specified
Tension range	15~70kgs
Roller speed (m/min)	10~40 adjustable
Standard arch (W x H mm)	850 x 600
Motor	AC
Sealing method	Heating element
Table height (mm)	805
Power supply	110/220/230/240V, 50/60Hz, 1PH 220/230/380/415/440V, 50/60Hz, 3PH
Power consumption (kw)	1.0
Layout dimension (L x W x Hmm)	1440 x 600 x 1530

*Specification subject to change without notice



JIA-IN INDUSTRY CO., LTD.

T +886 4 2359 4966

F +886 4 2359 2449

E info@joinpack.com

www.joinpack.com

