



A-93Y

Side Seal Automatic Strapping Machine

Description

Low-cost automation by integrate with conveyers.

Ideal for general industry.

Ideal designed for general industry and to be integrated by IN-LINE with other machines for general industry.

Various arch size combination and workability of different strap widths between 9 ~ 15 mm can serve all kinds of packages.

Tension range between 15~70 KGs and cycles speed 24 straps.

Available to equip with various unique options to perform advanced functions.

Features

- 8 digit counter
- Proximity cam switch
- Instant heating system
- Weld cooling time adjustable
- Digital regulator in PCB which LED shown I/O status

Options

- Top press
- Looping ejector
- Auto loading system
- Stainless steel housing
- Stacker light with buzzer
- Coil end strap ejecting out
- Up-stream and down-stream interlock
- Strapping sensor(photocell) with bracket

Specification

Speed (straps / min)	24
Strap width (mm)	9,12,15 specified
Tension range	15~70kgs
Standard arch (W x H mm)	600 x 850
Motor	AC
Sealing method	Heating element
Power supply	110/220/230/240V, 50/60Hz, 1PH 220/230/380/415/440V, 50/60Hz, 3PH
Power consumption (kw)	1.0
Layout dimension (L x W x Hmm)	1425 x 600 x 850

*Specification subject to change without notice



JIA-IN INDUSTRY CO., LTD.

T +886 4 2359 4966

F +886 4 2359 2449

E info@joinpack.com

www.joinpack.com

