



S-555N

High Performance, Equipped With Tension Indicator

Description

High performance equipped with digital indicator for electrical tension adjustment. Low voltage DC motor driven, perform fast speed and wide tension range at low noise.

Available for narrow and thick strap.

Table height adjustable.

Legs dismountable for saving transportation and storage cost.

Features

- Reliable tension system :
 - Big main roller driven by DC motor
 - Wide tension range from 3 to 40 kgs
- Various strap thickness and width workable:
 - Width: 5mm to 15 mm
 - Thickness: 0.4 mm
- Less mechanical parts, easy maintenance
- Easy to access track guide and main roller
- Front side tension adjustment with indicator
- PCB: Plug and play system, easy replacement
- Table height adjustable from 750mm to 830mm

Option: Table width:540mm

Specification

Cycle Time	2 sec / strap
Tension Range	3~40kgs
Strap Width	5,6,9,12,15.5 mm adjustment
Sealing Method	Heating element
Reel Inside Diameter	200, 230, 280mm specified
Power Supply	100/ 110/ 220/ 230/ 240V, 50/60Hz, 1PH
Table Height	750~830mm adjustable
Power Consumption	0.45kw
Machine Dimension	L845 x W430 x H750
Machine Weight	65 kgs

*Specification subject to change without notice

